

Ronen Consultancy Services

	Cisco	Allot	Sandvine	Procera	Huawei	ipoque	F5	Alcatel Lucent	Ericsson	Nokia Siemens Networks	Cisco
Category	Standalone DPI						ADC	Edge Router	GGSN		
Product	SCE 8000	Service Gateway – Sigma-E	PTS 24700	PL-20000	SIG 9800	PRX-10G	VIPRION 4800	7750 SR-12e (ISA Module)	SSR-8000	Flexi Network Gateway (NG)	ASR-5000
Platform	Proprietary	ATCA	Proprietary	ATCA	Proprietary	IBM BladeCenter	Proprietary	Proprietary	Proprietary	ATCA	Proprietary
											
Height	5U	13U	4U	14/15U (AC/DC)	32U	9U	16U	14U		13U	14U
Interfaces per chassis	2 or 4*0GE or 8-16*1GE	16 *10GE	8*10GE or 8*1GE	36*10GE or 2*100GE	1*10GE, 1*10G POS, 12*GE, 12*1000M 2*10GE, 20*GE	40*1/10GE	64*1/10GE 16*40GE	10x (1x100GE or 1xOC768 or 3x40GE or 12x10GE or 48x1GE)			

Ronen Consultancy Services

Throughput											
Blade	15 Gbps	32 Gbps				10 Gbps		10 Gbps		10 Gbps	
Chassis	30 Gbps	160 Gbps	120 Gbps	320 Gbps	120 Gbps	120 Gbps	320 Gbps	70 Gbps	400 Gbps		20Gbps
Cluster		1 Tbps	480 Gbps	5 Tbps					16 Tbps		
Uni-directional flows (chassis)	32M	100M chassis 10M Blade	72M	120M	96M	130M	72M	21M			
New Flows/second (chassis)	15M	150,000 (blade)	2M	2.4M	4.8M	2.5M	1.6M	490K			
Subscribers (chassis)	1M	8M	5M	10M	-	10M	96M	4M			2M